

lisa **SHAKE**[™]

ELISA Plate Shaker-Incubator



CE

Features

- Simultaneous orbital shaking & incubation operation
- Buzzer indication on completion of incubation
- Indication of Remaining Time
- Display of temperature on pressing TEMP Key

Technical Specifications

Operating Modes : Shaker, Incubator, Shaker & Incubator

TEMPERATURE CONTROL

Temperature Range : 37⁰ C to 42⁰ C

Resolution : 1⁰ C

STORAGE CONDITIONS

Temperature : From - 10⁰ C to 35⁰ C

Relative Humidity : Up to 80%

Dimensions in mm (lxbxh) : 280 X 250 X 160 (Approx)

Weight : 3 Kg (Approx)

Operating Position : On horizontal flat, rigid and vibration free surface

Incubation Time : 1 to 999 min


SHAKER

Frequency : 400 to 700 RPM

OPERATING CONDITIONS

Temperature : From + 18⁰ C to 32⁰ C

Relative Humidity : Up to 80%



RPM 400 TO 700



Incubator



Shaker

Due to continuous development, specifications are subject to change without prior notice.




ROBONIK (INDIA) PVT. LTD.

Plot No. 3 & 4, MIDC Industrial Area, Morivali, Near Ladi Naka,
Ambarnath (W) - 421 501, Thane, INDIA

Tel.: +91 (251) 2689000, Fax : +91 (251) 2689001,
National Sales : marketing@robonikindia.com,
International Sales : export@robonikindia.com



 1800 3000 84 94
www.robonik.in